

# RS-232 Series MEMS Inclinometer

The 2GIG RS-232 pitch and roll sensor is engineered to work for all applications. Our internal software provides unlimited programming capabilities that allow us to provide one of the easiest to use sensors on the market.



ENGINEERED TO PERFORM  
AT EVERY LEVEL

## ADAPTIVE SENSING TECHNOLOGY

### | STABILITY |

Combination of a 3-axis Accelerometer and 3-axis Gyroscope provides excellent stability under extreme environments

### | FILTER |

Custom filter using an advanced Kalman-based sensor fusion algorithm

### | RELIABILITY |

Polycarbonate enclosure with an epoxy encapsulated PCB allow this sensor to withstand extremes

### | ACCURACY |

Excellent dynamic accuracy for challenging conditions.



>Our RS-232 tilt sensor is the number one solution for any angular measurement application. Whether you simply need to obtain tilt readings with a PC or integrate within an industrial system, the RS-232 inclinometer is designed to be the perfect fit-and-forget solution or drop-in replacement.

- 0.1° of Accuracy with 0.01° Resolution
- Temperature Compensated
- Single Axis Measurement Range up to  $\pm 180^\circ$
- Dual Axis Measurement Range up to  $\pm 90^\circ$
- Horizontal or Vertical Mount Options
- Relative Zeroing via Button or RS-232 Command
- Adjustable baud rate and output rate (up to 100 Hz)
- Simple Installation, No moving parts or maintenance

>Rugged and robust design built with materials chosen for their ability to survive the harshest of environments and operating conditions. Featuring an anti-fungal housing with a protection class rating of IP67, these inclinometers are guaranteed to work with the highest accuracy in any industrial condition.


>Flexible lead times and top notch customer service allows us to put a 2GIG inclinometer in your hands when you need it. Our rapid communication and “on demand” supply method eliminates long lead times and ensures every customer is treated as the highest priority.

[www.2gig-eng.com](http://www.2gig-eng.com)

| 194 Main Road, Abbot, Maine USA 04406 | 207.876.4800



# RS-232 Series MEMS Inclinometer



## LEVELING THE WORLD

The RS-232 Inclinometer has a wide array of uses. Our team of engineers can work with you in order to create the sensor that fits your application. Whether its legacy units, drop-in replacements, or new applications, 2GIG can provide the correct settings for your application.

### AERIAL LIFTS



### CONSTRUCTION



### Input Protection Circuitry

- Reverse Polarity Protected
- Overvoltage Protected up to 60VDC
- CE Compliant Protection – Resists surges up to 500V and 250A

### Sensor Fusion Algorithm

Our advanced algorithm provides excellent dynamic accuracy for high vibrate and high acceleration conditions.

### RS-232 Transceiver

The sensor fusion algorithm readings are sent to an RS-232 transceiver and then provided to the user through protocol messages. The RS-232 message baud rate and output rate are adjustable via input commands.

### MARINE



### AUTOMATION



## Termination options

- Loose leads for direct wiring
- Serial DB9 plus DC power adapter



## Customize your inclinometer

- Marine-Grade Stainless or Aluminum enclosures
- Wiring or connector options
- Adjust the protocol messages and commands
- Pair with our HMI's for angular readout
- Use as a receiver with our wireless transmitters

### AGRICULTURE



### INDUSTRIAL



[www.2gig-eng.com](http://www.2gig-eng.com)

| 194 Main Road, Abbot, Maine USA 04406 | 207.876.4800

